

Shenzhen Sunvision Electronics Tech LTD

ADD: 4th floor 1st Building B Bolck Tangxi the second Industry Area ,Gushu, Xixiang, Baoan District,Shenzhen,China
Tel: +86-755-27918979 cell:86-13480916979

Geiger Muller tube List(glass)

Model no.	Size		Material	Technical parameter							working		Detecting object
	Outer Dim.	Total length		Recommendation work voltage	starting voltage maximum	range of pleateau area	Maximum Plateau Slope	Limit working voltage	background	temperature	Life time		
	mm	mm		V	V	V	%/V	V	Time/minute	(°C)	(pulse)		
J301γβ	10±0.5	205±3	glass	400	≤350	380-480	0.125	600	50	-40~+70	1*10 ⁹	γand β	
J302γβ	6.2±0.2	65±3	glass	390	≤350	-	-	500	-	-40~55	> 150hour	γand β	
J32γβ	6.5±0.5	34±2	glass	400	≤350	380-480	0.125	550	5	-20~50	1*10 ⁹	γand β	
J304γβ	10±0.5	90±2	glass	380	≤350	360-440	0.125	600	25	-40~55	1*10 ⁹	γand β	
J305γβ	10±0.5	107±3	glass	380	≤350	360-440	0.125	550	25	-40~55	1*10 ⁹	γand β	
J306γβ	18±1	197±3	glass	400	≤350	360-440	0.125	600	88	-40~55	1*10 ⁹	γand β	
J307γβ	14±1	197±3	glass	400	≤350	380-480	0.125	600	80	-40~55	1*10 ⁹	γand β	
J308γβ	18±1	143±3	glass	400	≤350	380-480	0.125	600	50	-40~55	1*10 ⁹	γand β	
M4011	10±0.5	90±2	glass	380	≤350	360-440	0.125	600	25	-40~55	1*10 ⁹	γand β	